



J A V E L I N

desktop card printers

CX-330 Re-transfer Printer & CL-500 Laminator



The innovative re-transfer card printer that gives you the finest photo quality available today

Features

- Perfect edge-to-edge printing, up to 125 cph
- Glossy photo finishing (no pre-printing required)
- Ideal for contact & contactless smart card desktop personalization
- Ability to print on a variety of card materials (PVC, PET, ABS, Polycarbonate, etc.) 0.76mm or 0.25mm thick
- Intelligent ribbon with Status Monitoring Program on PC
- Print head has no contact with card, minimizing risk of damage
- In-line operation of printing, encoding and lamination reduces total personalization time
- Security Erase function for the K panelPsec Protocol to encrypt and decrypt print data sent via network
- Meets a wide range of encoding and printing needs

Need to print high quality edge-to-edge graphics onto most types of plastic card? Need the option of laminating clear or high security holographic overlays onto one or both sides? If you answered "yes" to either of these questions, then the CX-330 re-transfer printer is your best option for high quality, desktop card production.

Now available with 10/100 Mbps Ethernet as standard, CX-330 is designed to personalize high quality, full-bleed, full-color magnetic stripe, contact, and contactless smart cards manufactured from PVC and a range of other

different materials. The CX-330 has a user-friendly LCD panel that displays machine status. For high security applications, this printer can be combined with the optional CL-500 laminator and CF-AT10 turning unit for in-line single or dual-sided lamination. The unique re-transfer process ensures that even uneven card surfaces can be printed without a blemish.

**... high speed with the finest
photo quality and optional added
security and durability ...**





CX-330 Re-transfer Printer CL-500 Laminator Technical Details

GENERAL SPECIFICATIONS

- **Printing Method**
Dye Sublimation / Resin thermal transfer
- **Resolution**
300 dpi
- **Printable area**
Full-bleed
- **Print Speed**
29 seconds per card
- **Lamination speed**
20 seconds per side
- **Interface**
 - USB 2.0
 - Ethernet 10/100 Mbps (IPSec IPv4 security protocol)
- **Driver**
Windows® drivers for XP, Vista & 2000
- **Dimensions (W x H x D)**
Printer: 343mm x 381mm x 339mm
Laminator: 207mm x 308mm x 311mm
Turning unit: 110 mm x 254 mm x 241 mm
- **Weight**
Printer: 22kg
Laminator: 8kg
Turning unit: 3.2kg
- **Signal Level**
256 levels per color (YMC); 2 levels (K)
- **Hopper Capacity**
300 cards (0.76mm thickness)
- **Stacker Capacity**
100 cards (0.76mm thickness)


- **Ink Ribbon**
 - YMCK ink ribbon set (1000 sides per set)
 - YMCKK ink ribbon (750 cards per roll)
 - YMCKUv ink ribbon (750 sides per roll)
 - Retransfer film (1000 sides per roll)
- **Lamination Film**
 - Clear patches (600 patches per roll)
 - Holographic Overlay (1000 sides per roll)
- **Options**
 - Magnetic Stripe Encoding (300/2750 oe)
 - Contact & Contactless smart cards
 - Lamination unit (single or dual-sided)
 - Turning unit (for dual-sided lamination using different laminates on top and bottom of card)
- **Safety Standards**
UL, VCCI-B, FCC Class B, EN Class B

Genuine NBS Supplies

Your choice of card printer supplies is critical. It is a primary factor affecting the reliability and consistency of printing. Genuine Javelin Supplies meet stringent quality standards and are tested for optimum performance with Javelin card printers.



Card Hopper holds up to 300 cards (0.76mm)



Optional, field-upgradeable lamination unit



Optional in-line contactless smart card encoding module



Re-transfer printing process
First, the card design is printed in color onto the reverse of the clear re-transfer film. The printed film is then released from its carrier and applied to either side of a plastic card



Corporate Headquarters
Canada
703 Evans Avenue
Toronto, Ontario
M9C 5E9
Canada
tel: +1 416.621.1911
fax: +1 416.621.8875

**Contact your nearest NBS location
for more information on Javelin™
card printers & consumables:**

Europe, Middle East, Africa
B1 Moorfield Point
Slyfield Industrial Park
Guildford, Surrey GU1 1RU
United Kingdom
tel: +44 (0)1483 963200
fax: +44 (0)1483 511189

North / South America
10925 Bren Road E
Minneapolis, MN 55343
USA
tel: +1 416.840.8620
fax: +1 952.912.9439

Asia Pacific
PO Box 780
Hurstville BC
NSW 1481
Australia
tel: +61 (2) 9546 6841
fax: +61 (2) 9546 6851

Website: www.nbstechn.com
Email: info@nbstechn.com

©Feb 2009 NBS Technologies Inc. Specifications are subject to change without notice. All rights reserved. NBS and the NBS logo are registered trademarks of NBS Technologies Inc. in the United States and Canada and are trademarks in other countries. Javelin is a registered trademark of NBS Technologies Limited in the United States and European Union and are trademarks in other countries. All other brand and product names are the trademarks or registered trademarks of their respective holders.